TECHNICAL SPECIFICATION



K2™ 3-Point Harness

K2™ 3-Point Harness / FAR0402



DESCRIPTION

The premium $K2^{TM}$ harness range combines quality materials with innovative features for optimum ergonomic performance, comfort, and safety.

This harness has a work positioning belt, parking loops and quick release buckles, with air mesh material and lightweight aluminium connectors.

OPTIONS

K2™ 3-Point Harness (FAR0402)

SAFETY STANDARDS

EN 361 • EN 358















SPECIFICATIONS

Anchorage Points

2

Fall Indicator

No

Work Postioning Belt

Yes

Lanyard Parking

Yes

Sub-Pelvic Strap

Yes

Metal Parts

Light Alloy Steel



Product Weight 2210g

FEATURES



Quick Release Buckles

Quick release buckles for quick and effortless fitting.



Tool Keepers

K2[™] 3-point and 5-point harnesses feature tool keepers for safely stowing tools.



Lanyard Keepers

Breakaway clips safely store unused lanyards and release in the event of a fall.



Adjustment

Tool Keeper

Comfort Padding

Product Label Protected

Rated Weight / Load

Yes

Yes

Yes

140kg

Shoulder, Chest and Legs

Quick Release Buckles

Breathable Material

Air mesh material gives harnesses breathability and anti-tangle feature.



Inspection Labels

Inspection labels and user information protected in PVC pouch.



Ultimate Comfort

Polyester padding in leg, back and waist areas for improved comfort.

RANGE



VIDEOS

youtu.be/_QUfxDLufkA

DOWNLOADS









JSP Limited. Worsham Mill. Minster Lovell. Oxford OX29 0TA. England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com





