# **ASKYTEC TRC725**

# LIGHTWEIGHT, OPEN FINGERS DESIGN PU COATED GLOVE WITH STEEL FIBRE AND RECYCLED POLYESTER

Outstanding cut resistance allowing protection in the most risky applications whilst enabling precise handling in applications necessitating open fingertip contact. PU coating protects the hand from abrasion and grease, delivering effective long lasting grip.

## FEATURES

- > Cut resistant: Level E / ANSI A5
- A flexible and comfortable glove offering great dexterity
- > HPPE on the inside provides comfort and protection
- Fully encapsulated steel with recycled polyester on the outside strengthens the protection against burrs and sharp edges
- PU coating gives exceptional abrasion resistance and sensitivity allowing workers to handle small pieces
- > Three open fingers to allow high precision tasks
- > Seamless knit prevents irritation
- > RCS (Recycled Claim Standard) certified
- > 1 pair = 1 PET bottle of 500ml recycled
- > 8g of CO<sub>2</sub> reduced vs virgin polyester alternative



# SUITABLE FOR

## **Typical Industries**

- Automotive
- Construction
- Logistics
- Maintenance
- Manufacturing
- Transport

## **Suitable Applications**

- Assembly
  Usedling short
- Handling sharp and greasy parts
- Machining
- Bodywork
- Precision mechanics

# CERTIFICATION



See overleaf for explanation





CUT PROTECTION

#### **PRODUCTION INFORMATION**

MATERIALS	LINER:	13 gauge HPPE, steel fibre, recycled polyester	
	COATING:	Polyurethane (PU)	
COLOUR	Green/black		
LENGTH (mm)	250 (Size Dependent)		
CUFF STYLE	Elasticated knit wrist		

#### **ORDERING DETAILS**

SIZE	CODE	PACKAGING
6/XS 7/S 8/M 9/L 10/XL 11/XXL	SKG00017EB SKG00017ED SKG00017EF SKG00017EH SKG00017EJ SKG00017EL	10 pairs per paper wrap 120 pairs per case

### **CERTIFICATION** LEGENDS



MECHANICAL HAZARDS EN 388:2016 PERFORMANCE LEVELS*						
0-4	0-5	Tear F	0-4 Punc Resistance Cut Resist	Straig ture Resist	P I Impact Resistance ht Blade Cut Resistance (EN ISO: 13997 ance	

Abrasion Resistance

\*If tests are not performed or are not applicable, 'X' will be placed instead of a number/letter

CLASSIFICATION FOR CUT RESISTANCE					
Measured breakthrough time	Permeation performance index (grams)				
A1	≥ 200				
A2	≥ 500				
A3	≥ 1000				
A4	≥ 1500				
A5	≥ 2200				
A6	≥ 3000				
A7	≥ 4000				
A8	≥ 5000				
A9	> 6000				

**GLOBUS AMERICAS** 

www.globusgroup.com

E: americas@globusgroup.com

GLOBUS

#### **EUROPE**

#### www.globusgroup.com

- E: sales@globus.co.uk
- T: +44 (0)161 877 4747
- F: +44 (0)161 877 4746

#### **MIDDLE EAST & AFRICA**

#### www.globusgroup.com/gcc

- E: gcc@globusgroup.com
- T: +97148829962
- F: +97148829963

Globus Group, T2 Trafford Point, Twining Road, Trafford Park, Manchester, M17 1SH, UNITED KINGDOM Globus EMEA FZE, Jafza One, Tower A, Office 2201, Jebel Ali, PO Box 61195, Dubai, UNITED ARAB EMIRATES Globus Americas LLC, 45 Rockefeller Plaza, Suite 2000, New York City, New York, 10111, USA

© 2023 Globus (Shetland) Ltd | SKY-DATA-TRC725-1123\_1

EU compliance certificate delivered by the notified body INTERTEK ITALIA SPA, Via Guido Miglioli, 2/A - 20063 Cernusco sul Naviglio (MI) - Italia (Notified Body No. 2575)

The descriptions, characteristics, applications and photos are given for information purposes and do not constitute a contractual commitment. The manufacturer reserves the right to make any modifications it deems necessary.

### **RECOMMENDATIONS FOR USE**

- USE: General handling glove with cut protection. Not suitable for thermal, electrical, chemical protection. Do not use near moving machines if there is a risk of entanglement
- STORAGE: Store in dry conditions in the original packaging and away from direct sunlight
- CLEANING: To clean, wipe with a damp cloth. Note: The performance characteristics of worn and laundered gloves may differ from the results shown Inspect the gloves to ensure no damage is present
- LIFETIME: Service life depends on the glove application and therefore cannot be specified. It is the responsibility of user to ensure the glove is suitable for its intended use