

EG704T

ANSI • CE/UKCA •

Low-profile, modern sport design with anti-glare frame // Direct ventilation // Adjustable elastic band and soft PVC frame // Passes EN166 3 & 4, liquid droplets and large dust

Gray Body with Black Strap | 1 Variations

● EG704T ● ● Clear AF



General Specifications

Weight: 35 gm
 Bridge: 21 mm
 PD: 64 mm
 Lens base: 6 curve
 Lens size diagonal: 82 mm
 Lens size vertical: 52 mm
 Lens thickness: 2.2 mm
 Overall Width (Hinge-Hinge) : 148 mm

Materials

Lens: polycarbonate
 Body: polyvinyl chloride
 Headband: nylon

Part No.

EG704T

Lens Markings

2C-1.2 P 1 BT CE

Frame Markings

P EN166 3 4 BT CE UKCA

Lens Marking Symbols

Code - field of use
 2 or 3: UV filter
 5 or 6: Solar filter
 Color perception
 C: Unimpaired color perception
 Protection class
 1.2 - 6: Degree of visible light filtration
 Optical class
 1: High optical quality - no optical distortion
 Mechanical Strength
 B: Medium energy impact, resists a 6mm, 0.86g at 120 m/s
 T: Impact protection at extreme temperature conditions
 Symbols
 P: Manufacturer's mark
 N: Filter with anti-fog
 CE: Certification for European Union

Frame Marking Symbols

Symbols
 P: Manufacturer's mark
 EN 166: CE specification for protective eyewear
 3: Liquid droplets or splashes
 4: Large dust particles
 CE: Certification for European Union
 UKCA: Certification for United Kingdom
 Mechanical Strength
 B: Medium energy impact, resists a 6mm, 0.86g at 120 m/s
 T: Impact protection at extreme temperature conditions