

Solo[®] ANSI • CE • CSA •

Temples are vented to reduce fogging // Custom imprinting available

Lens and Temples | 4 Variations

- S510S Clear
- S510SD Clear Dispenser pack – 12 per box



General Specifications

Weight: 46 gm
 Lens base: 4 curve
 Lens size diagonal: 145 mm
 Lens size vertical: 45 mm
 Lens thickness: 2 mm
 Overall length (lens - tip): 108 mm
 Overall width (hinge - hinge): 159 mm

Materials

Lens: polycarbonate
 Frame: polycarbonate
 Temples: polycarbonate
 Side Shield: polycarbonate
 Hinge: polycarbonate
 Nosepiece: polycarbonate

Part No.

S510S
 S510SD

Lens Marking

P Z87+ U6
 P Z87+ U6

Temple Marking

P Z87 + / P c SEI Z94.3
 P Z87 + / P c SEI Z94.3

Lens Marking Symbols

P: Manufacturer's mark
 Z87: ANSI standard for eye and face protection devices
 +: High impact
 UV Filter Transmittance
 U6: .01% max effective far UV • .1% max near UV

Temple Marking Symbols

P: Manufacturer's mark
 Z87: ANSI standard for eye and face protection devices
 +: High impact
 c SEI Z94.3: CAN/CSA standard for eye and face protection devices